

## **CNC LATHE (JN-CH506MSY)**

# Technical Document

By Jiangnan CNC Machine Co., Ltd.

By Jiangnan Technology (Songyang) Co., Ltd.

Party A: :

Party B: Jiangnan CNC Machine Tool Co., Ltd.

Date:

Date:

## 1. Company Profile



Jiangnan CNC Machine Tool Co., Ltd. is located in the beautiful coastal city of Wenzhou, China. It is a CNC machine manufacturing enterprise integrating research, design, manufacturing, and sales. The company was established in September 2006 and currently has a standardized plant covering an area of 85,000 square meters, with more than 180 excellent staff members. Among them, 90 employees have a college degree or above, accounting for 50% of the total staff; the company has 20 research and development personnel, accounting for 9% of the total workforce.

Adhering to the business philosophy of "technological innovation, win-win cooperation, integrity and efficiency, sincere service," and the quality policy of "quality first, customer foremost," the company provides customers with the most cost-effective products and comprehensive services, aiming to create the maximum value for customers. With advanced equipment including the world's most advanced large-scale CNC five-axis machining center and horizontal machining center, as well as contour grinding machines and high-precision Renishaw inspection equipment, the company strictly adheres to international standards. It has obtained ISO9001 certification and implements rigorous process inspections to ensure product quality.

The company mainly manufactures vertical Machining Centers, horizontal Machining Centers, drilling and tapping machine, gantry series, CNC lathes, and other series of products:

1. Vertical Machining Centers: JN-IV850, JN-NV856, JN-NV900, JN-NV1050, JN-IV1160, JN-NV1300, JN-NV1690, etc.
2. Horizontal Machining Centers: JN-H50, JN-IH50, JN-H63, JN-IH63, JN-H800, JN-H1810, etc.
3. Drilling and Tapping Machines: JN-T500, JN-T700, etc.
4. CNC Lathes: JN-CH106, JN-CH108, JN-CH108M, JN-CH108MY, JN-CH208, JN-CH506MSY, etc.
5. Gantry Series: JN-GL2013, JN-GL2015, JN-GL2518, JN-GL2720, JN-GL3023, JN-GL4023, JN-GL4027, JN-GL5030C, etc.

Our machine tools are popular in major provinces and cities in China, including Beijing, Shanghai, Chongqing, Tianjin, Hebei, Henan, Shanxi, Shandong, Jiangsu, Zhejiang, Guangdong, Anhui, Hubei, Fujian, and others, due to their excellent performance and first-class after-sales service. The company adopts a combination of direct sales and distributorship models and has cooperated with 100 distributors nationwide, covering major cities across the country.

Jiangnan CNC – A national brand, a national pride! We sincerely invite you to join with us to create a new era of high-tech machinery!

## 2.Introduction the Songyang Factory



Jiangnan Technology (Songyang) Co., Ltd., a wholly-owned subsidiary of Jiangnan CNC Machine Tool Co., Ltd., was established in August 2017. Located in the beautiful scenic city of Songyang, Lishui, it covers an area of 107.69 acres with a total construction area of 29,693 square meters. The company has a registered capital of 50 million yuan, with fixed asset investment of 300 million yuan and working capital investment of 70 million yuan. It has introduced multiple sets of high-precision equipment such as the Japanese DAIWA CNC gantry five-axis machining center and horizontal machining centers.

Building on the development foundation of its parent company, Jiangnan Technology actively promotes brand building and product serialization strategies. Internally, it implements ERP systems and information construction, optimizing business processes, and enhancing the company's management level and core competitiveness. Facing the challenges of economic globalization, Jiangnan will continue to focus on the CNC machining center industry, adhere to market-oriented business philosophy, and persist in the direction of "internationalization, technologicalization, and industrialization." It will vigorously introduce advanced equipment, technology, and talents, integrate resources, leverage strengths, and strive to shape "Jiangnan" into a well-known enterprise in the international CNC machining center industry.

### 3.The technical parameters of the JN-CH506MSY

NO.	Item	Unit	Specification
1	Max. swing over bed	mm	300
2	Max. turning length	mm	650
3	Spindles		2
4	Spindle speed	r/min	30~6000
5	Spindle nose taper		A2-5
6	Spindle bore		46
7	Tool holder	set	2
8	X1 axis travel	mm	800
9	X2 axis travel	mm	800
10	Y1 axis travel	mm	220
11	Y2 axis travel	mm	220
12	Z1 axis travel	mm	600
13	Z2 axis travel	mm	600
14	Rapid feed	mm/min	24000
15	Cutting feed	mm/min	10000
16	Left turret turning tools		5
17	Right turret turning tools		4
18	Left turret milling tools		4

19	Right turret milling tools		4
20	OD tools size	mm	16* 16
21	Boring tools diamater	mm	20
22	CNC system		SYNTEC
23	Spindle (max. torque)	N.M	125
24	X-axis motor (max. torque)	N.M	11
25	Z-axis motor (max. torque)	N.M	18.6
26	Y-axis motor (max. torque)	N.M	11
27	Sub spindle(max. torque)	N.M	11
28	Spindle (Power)	kw	17.5
29	X-axis motor (power)	kw	2.4
30	Z-axis motor (power)	kw	3.9
31	Y-axis motor (power)	kw	2.4
32	Sub spindle(power)	kw	2.3
33	Voltage	V	220
34	Frequency	Hz	60
35	Air pressure	Mpa	0.5
36	Oil pressure pump	Kw	1.5
37	Lubricating oil pump	Kw	0.004
38	Water pump	Kw	0.37
39	Power supply	Kva	20
40	Machine size (L*W*H)	mm	3036 * 1982*2157

The actual values for power supply, air pressure source, machine weight, and overall dimensions may vary due to different configurations and peripheral equipment.

#### 4.Detailed supplier of main components

ITEM	SPEC	BRAND ORIGIN	BRAND	ITEM
CNC Control System		22TB	Taiwan	SYNTEC
Servo Motors	X-axis	AM11	Taiwan	SYNTEC
	Y-axis	AM11 with holding brake		
	Z-axis	AM18		
	Power head	AM11*		
Ball Screws	X-axis	φ32	Japan	THK
	Y-axis	φ32		
	Z-axis	φ40		
Linear Guide	X-axis	35	Japan	THK
	Y-axis	35		
	Z-axis	35		
Screw Couplings	X-axis	ALS-055-R-20B-24B	Japan	THK
	Y-axis	ALS-055-R-20B-24B		
	Z-axis	ALS-055-R-25B-35B		

Ball Screw		S6206	Japan	NTN
Bearing		S7206		
Spindles		A2-5-170-D-02		CHNCIT
Transformer		20KWA	Joint Venture	LUHO
Powerheads		TX-ER25-YT150-P4	Taiwan	JANETECH
Electrical Components			Germany	SCHNEIDER
Pneumatic Components			Japan	SMC
Lubrication System			China-Japan Joint Venture	HEGU
Shield		Retractable Shield	China	CHNCIT
		Roller shutter shroud	China	CHNCIT
Chip Conveyor		Chain Plate Type Chip Conveyor	China	CHNCIT

Note: If any supplier fails to supply, it will be replaced with a brand of equal quality without further notice.

## 5. Optional accessories list

No.	Name	Quantity/Unit	Note
1			
2			
3			
4			
5			
6			
7			
8			

## 6. Tools and manuals list

No.	Name	Quantity/Unit	Remarks
1	Toolbox	1Set	
2	Certificate of conformity	1Copy	
3	Machine specification	1Set	
4	System specification	1Set	
5	Air gun	1 Piece	

## 7. Machine Mechanical Indicators

### 1、 Machine Structure

Machine Structure The main structural components of the machine tool are made of high-tensile cast iron, optimized in design for high static rigidity. The spindle features a high-rigidity structure, high mechanical efficiency, suitable for high-precision heavy cutting machining. The spindle motor adopts AC servo technology, enabling stepless speed regulation in both forward and reverse directions. The three-axis ball screw and servo motor drive directly, with no transmission cumulative error, ensuring high repeatability and positioning accuracy. Automatic tool changing structure, quick and smooth tool changing operation. All machine components and various measurement units comply with international (ISO) standards.

### 2、 Machine Protection

Machine Protection The machine protection device is safe, complete, and reliable. Machine noise: in compliance with national standards, 75dB. Electrical control cabinet sealed to prevent dust and water, IP65 rating.

### 3、 Lubrication System

Lubrication System Adopts TZ electric lubrication device to quantitatively lubricate all sliding surfaces and ball screws. Adjustable lubrication time intervals and amounts to ensure 100% lubrication at all lubrication points. Machine displays an alarm in case of low oil level (oil shortage). Uses 68# guide rail lubricating oil. Lubrication tank capacity: 2 liters. Lubrication pump voltage: 220V, motor output power: 25W, maximum pressure: 2.5MPa, discharge flow rate: 110ml/min.

### 4、 Pneumatic System

Pneumatic System Pneumatic system, pressure switches, solenoid valves, etc., realize pneumatic tool changing, pressure: 6-8KG/C m<sup>2</sup>, flow rate: 220L/MIN, can clean the working area.

### 5、 Electrical System

Electrical System The standard system has complete and reliable interlocking, safety protection, and fault self-diagnosis alarm functions. Equipped with RS232 standard communication interface, can use computer floppy disk for program storage. (Other systems can be provided according to user requirements).